


CANELA

ECO-TURN




48..

Reference Bezeichnung	D5m	L1	L2	Insert size Wendeschneidplatte			Nm
PSC40-4824.16-2.25D	40	65	36,0	XCMT 0804..	1330	5508	0.8
PSC40-4834.20-2.25D	40	75	45,0	XCMT 10T3..	1235	5515	3.0
PSC40-4844.25-2.25D	40	90	56,5	XCMT 1304..	1250	5520	4.0
PSC50-4824.16-2.25D	50	65	36,0	XCMT 0804..	1330	5508	0.8
PSC50-4834.20-2.25D	50	75	45,0	XCMT 10T3..	1235	5515	3.0
PSC50-4844.25-2.25D	50	90	56,5	XCMT 1304..	1250	5520	4.0
PSC63-4824.16-2.25D	63	65	36,0	XCMT 0804..	1330	5508	0.8
PSC63-4834.20-2.25D	63	75	45,0	XCMT 10T3..	1235	5515	3.0
PSC63-4844.25-2.25D	63	90	56,5	XCMT 1304..	1250	5520	4.0

XCMT

Square positive insert with 7° clearance.
Vierkantige positive Wendeschneidplatte mit 7° Freiwinkel.

Reference / Bez.	l	s	d	r
XCMT 080304-MP EN	8,40	3,18	8,40	0,4
XCMT 10T308-MP EN	10,40	3,18	10,40	0,8
XCMT 130408-MP EN	13,34	4,70	13,34	0,8



XCMT



Eines CANELA, S.L.

Pol. Ind. "Les Guixeres" · Torrent de Vallmajor 88 · 08915 Badalona · Catalunya · Espanya · Tel. +34. 93 399 85 61 · www.canelatools.com