



CANELA ECO-TURN



48.. 

Riferimento Referencia	D5m	L1	L2	Dimensioni inserto Medida plaquita			Nm
PSC40-4824.16-2.25D	40	65	36,0	XCMT 0804..	1430	5508	0.8
PSC40-4834.20-2.25D	40	75	45,0	XCMT 10T3..	1235	5515	3.0
PSC40-4844.25-2.25D	40	90	56,5	XCMT 1304..	1250	5520	4.0
PSC50-4824.16-2.25D	50	65	36,0	XCMT 0804..	1430	5508	0.8
PSC50-4834.20-2.25D	50	75	45,0	XCMT 10T3..	1235	5515	3.0
PSC50-4844.25-2.25D	50	90	56,5	XCMT 1304..	1250	5520	4.0
PSC63-4824.16-2.25D	63	65	36,0	XCMT 0804..	1430	5508	0.8
PSC63-4834.20-2.25D	63	75	45,0	XCMT 10T3..	1235	5515	3.0
PSC63-4844.25-2.25D	63	90	56,5	XCMT 1304..	1250	5520	4.0

XCMT

Inserti quadrati positivi con angolo di spoglia 7°.
Plaquetas cuadradas positivas con 7° incidencia.

Riferimento / Referencia	l	s	d	r
XCMT 080304-MP EN	8,40	3,18	8,40	0,4
XCMT 10T308-MP EN	10,40	3,18	10,40	0,8
XCMT 130408-MP EN	13,34	4,70	13,34	0,8

