

SET *ADMT*

MILLING CUTTER CONCAVE RADIUS INSERT SET ADMT1503

SET = 2 PCS 1-TOOTH MILLING CUTTERS WITH CONCAVE RADIUS + 18 PCS INSERTS



1235.01

Reference		d	D	L	L2	rmin	rmax	Insert size
1235.01.01701	1	16	17	120	30	1,0	2,5	ADMT 1503R1.0 / 2.5
1235.01.01703	1	16	17	120	30	3,0	5,0	ADMT 1503R3.0 / 5.0

ADMT-R

Inserts with 15° clearance

Reference	l	r	s	d
ADMT 1503R1.0	15,00	1.0	3,18	9,52
ADMT 1503R1.5	15,00	1.5	3,18	9,52
ADMT 1503R2.0	15,00	2.0	3,18	9,52
ADMT 1503R2.5	15,00	2.5	3,18	9,52
ADMT 1503R3.0	15,00	3.0	3,18	9,52
ADMT 1503R3.5	15,00	3.5	3,18	9,52
ADMT 1503R4.0	15,00	4.0	3,18	9,52
ADMT 1503R4.5	15,00	4.5	3,18	9,52
ADMT 1503R5.0	15,00	5.0	3,18	9,52



TIN25

Coating composition



TiN-TiC-TiN

Coated with TiN-TiC-TiN. The CVD coating has a thickness of 3-5 microns for use on steel, alloyed steel and stainless steel, with or without coolant.