

SET *SDQC*

SET INTERNAL TURNING 107° 30'

Set of multipurpose profiling boring bars equipped with rhombic positive insert (angle 55°)

FOR GENERAL APPLICATIONS, ROUGHING, SEMI-FINISHING AND FINISHING

COOLANT





1 SET OF 3 BORING BARS

SET SDQC 107°30'

Riferimento Referencia	D	d	L1	L2	f	A	h	Dimensioni inserto Medida plaquita	
A0810J SDQC R/L 07	10	8	110	32	7	12,5	9	DC.. 0702..	0,350
A1012K SDQC R/L 07	12	10	125	38	9	15,5	11	DC.. 0702..	
A1216M SDQC R/L 07	16	12	150	50	11	19,5	15	DC.. 0702..	

Riferimento Referencia			Nm
A0810J SDQC R/L 07			0.9
A1012K SDQC R/L 07			0.9
A1216M SDQC R/L 07			0.9



DC..			
Inserti romboidali positivi 55° con angolo di spoglia 7° Plaquitas rómbicas positivas 55° con 7° incidencia.  A35			
Riferimento / Ref.	l	s	d
DC.. 0702..	7,75	2,38	6,35



DCGT-AL	DCGT-AP
	
DCMT	DCMW
	